

## Blowguns of series W 5



**schütze**  
SPRAYTECHNOLOGY





W 5/P/50



W 5/PB 212

Excellently suitable for blowing, dusting and cleaning of workpieces and all further equipment.

Longer pipes available.

Standard air connection = nipple for quick coupler (other connections on request). Further special designs on request. Technical alterations reserved.

For further information please contact us.

**fig. W 5/P/50 with 50 mm pipe**

also available with 100, 200 or 250 mm pipe

**W 5/P/S with rebound guard**

recommended by professional associations for industrial safety

**W 5/P/T with turbo nozzle**

The induction air gives approx. triple the air volume.

Less air consumption reduces the costs of blow air.

Also reduced rebound and larger applications.

**W 5/P/G with silencer nozzle**

reduce the noise level.

**W 5/G with rebound guard**

recommended by professional associations for industrial safety

Available standard versions:

**W 5/P/50** blowgun with 50 mm pipe

**W 5/P/100** blowgun with 100 mm pipe

**W 5/P/200** blowgun with 200 mm pipe

**W5/P/250** blowgun with 250 mm pipe  
(straight ahead or bended)

**W5/P/S** blowgun with rebound guard and 50 mm pipe

**W 5/P/F** blowgun with flat nozzle and 100 mm pipe

**W 5/P/T** blowgun with turbo nozzle

**W 5/P/G** blowgun with silencer nozzle and 50 mm pipe

**W 5/PB 212** blowgun with venturi nozzle,  $\varnothing$  18 mm

**W 5/PB 512** blowgun with venturi nozzle,  $\varnothing$  8 mm

**W 5/G** blowgun with straight handle with 50 mm pipe

Special designs on request.  
Technical alterations reserved.  
For further information please contact us.